




BO-JIANG


帛江科技股份有限公司

BO-JIANG TECHNOLOGY CO., LTD.

PRODUCT SPECIFICATION (產品規格)

PART NO.(圖號)	7011NS509BF000R	DATE (日期)	2007/03/05
TITLE(產品名稱)	BNC CRIMP PLUG		
MATERIAL AND FINISH(材質及表面處理)			
DESCRIPTION(名稱)	MATERIAL(材質)	FINISH(表面處理)	
Center Contact(中心導體)	BRASS	3u" GOLD	
Insulator(絕緣體)	TEFLON	WHITE	
Outer Contact(外導體)	BRASS	70u" NICKEL	
Others(其它)			
ELECTRICAL(電氣特性)			
Impedance(阻抗)	50 Ω		
Voltage Standing Wave Ratio(VSWR;駐波比)	1.3 Max. 0 - 4 GHz		
Dielectric Withstanding Voltage(絕緣耐電壓)	1500 Volts Min. RMS		
Contact Resistance (導體阻抗)	Center Contact (中心導體)	3 Milliohms Max.	
	Outer Contact (外導體)	2 Milliohms Max.	
Insulation Resistance(絕緣阻抗)	5000 Megohms min.		
MECHANICAL(機械特性)			
Force To Engage/Disengage(接合力/脫離力): 2.5 in-lbs max. / 3 lbs max.			
Coupling Nut Retention(聯結螺帽承受力): 100 lbs. min.			
Coupling Proof Torque(聯結承受扭力): N/A			
Contact Retention(中心導體承受力): 6 lbs. min.			
REMARKS(備註)			
1. Working Voltage (工作電壓) = 500 VRMS max.			
2. Temperature Range (操作溫度) = -65°C thru 165°C			

APPROVED:  2007/03/05

REVIEWED: 

DRAFTED: Avel 2007/03/05