



BO-JIANG

帛江科技股份有限公司

BO-JIANG TECHNOLOGY CO., LTD.

PRODUCT SPECIFICATION (產品規格書)

PART NO.(圖號)	7061FS501CF001B	DATE (日期)	2009/09/22	
TITLE(產品名稱)	BNC PANEL CRIMP JACK			
MATERIAL AND FINISH(材質及表面處理)				
DESCRIPTION(名稱)		MATERIAL(材質)	FINISH(表面處理)	
Center Contact(中心導體)		BRASS	GOLD FLUSH	
Insulator(絕緣體)		DELIN	WHITE	
Outer Contact(外導體)		BRASS	70 μ" NICKEL	
Others(其它)				
ELECTRICAL(電氣特性)				
項目		測試條件	測試規格	
Impedance(阻抗)		0 ~ 4 GHz	50 Ω	
Voltage Standing Wave Ratio(VSWR)(駐波比)		0 ~ 4 GHz	1.5 Max.	
Dielectric Withstanding Voltage(絕緣耐電壓)		DC , time: 60sec	1500 Vrms Min	
Contact Resistance (導體阻抗)	Center Contact (中心導體)	DC 0.2V, 1A	3 mΩ Max.	
	Outer Contact(外導體)	DC 0.2V, 1A	2 mΩ Max.	
Insulation Resistance(絕緣阻抗)		DC 500V, time: 60sec	5000 MΩ Min.	
MECHANICAL(機械特性)				
項目		測試條件	測試規格	
Force To Engage/Disengage(接合力/脫離力):		N/A	2.5 in-lbs max. / 3 lbs max.	
REMARKS(備註)				
<ol style="list-style-type: none"> Between BODY (NO.1) And LOCK RING (NO.3) Must Withstand A 18 lbs. Min. Axial Force. (軸向力測試)。 Between BODY (NO.1) And PANEL (NO.4) Must Withstand A 40 lbs. Min. Axial Force And A 15 in-lbs. Min. Torque Force. (軸向力和扭力測試)。 Cable Retention (纜線承受力): 20 lbs. Min. Or When Cable Gets Broken。 				
				
A	N/A			
Issue 版本	Revision 修改記錄	Approved 核准	Checked 審核	Drawn 製定