



帛江科技股份有限公司

BO-JIANG TECHNOLOGY CO., LTD.

PRODUCT SPECIFICATION (產品規格書)

BO-JIANG

PART NO.(圖號)	7061FS509CF001B	DATE (日期)	2009/09/22
--------------	-----------------	-----------	------------

TITLE(產品名稱)	BNC PANEL CRIMP JACK		
-------------	----------------------	--	--

MATERIAL AND FINISH(材質及表面處理)

DESCRIPTION(名稱)	MATERIAL(材質)	FINISH(表面處理)
Center Contact(中心導體)	BRASS	GOLD FLUSH
Insulator(絕緣體)	DELRIN	WHITE
Outer Contact(外導體)	BRASS	70 μ" NICKEL
Others(其它)		

ELECTRICAL(電氣特性)


項目	測試條件	測試規格
Impedance(阻抗)	0 ~ 4 GHz	50 Ω
Voltage Standing Wave Ratio(VSWR)(駐波比)	0 ~ 1 GHz	1.5 Max.
Dielectric Withstanding Voltage(絕緣耐電壓)	DC, time: 60sec	1500 Vrms Min
Contact Resistance (導體阻抗)	Center Contact (中心導體)	DC 0.2V, 1A
	Outer Contact(外導體)	DC 0.2V, 1A
Insulation Resistance(絕緣阻抗)	DC 500V, time: 60sec	5000 MΩ Min.

MECHANICAL(機械特性)

項目	測試條件	測試規格
Force To Engage/Disengage(接合力/脫離力):	N/A	2.5 in-lbs max. / 3 lbs max.

REMARKS(備註)

- Between BODY (NO.1) And LOCK RING (NO.3) Must Withstand A 18 lbs. Min. Axial Force. (軸向力測試)。
- Between BODY (NO.1) And PANEL (NO.4) Must Withstand A 40 lbs. Min. Axial Force And A 15 in-lbs. Min. Torque Force. (軸向力和扭力測試)。
- Cable Retention (纜線承受力): 10 lbs. Min. Or When Cable Gets Broken。



A	N/A	<i>Mark</i>	<i>Mark</i>	<i>Amel</i>
Issue 版本	Revision 修改記錄	Approved 核准	Checked 審核	Drawn 製定