



帛江科技股份有限公司

BO-JIANG TECHNOLOGY CO., LTD.

PRODUCT SPECIFICATION (產品規格書)

PART NO.(圖號)	7065NR502BF001R	DATE (日期)	2009 / 09 / 22
--------------	-----------------	-----------	----------------

TITLE(產品名稱)	BNC R/A PCB RECEIPT JACK		
-------------	--------------------------	--	--

**MATERIAL AND FINISH(材質及表面處理)**

DESCRIPTION(名稱)	MATERIAL(材質)	FINISH(表面處理)
Center Contact(中心導體)	BRASS	GOLD FLUSH
Insulator(絕緣體)	TEFLON	WHITE
Outer Contact(外導體)	BRASS	70u" NICKEL
Others(其它)		

**ELECTRICAL(電氣特性)**

項目	測試條件	測試規格	
Impedance(阻抗)	0 ~ 4 GHz	50 Ω	
Voltage Standing Wave Ratio(VSWR)(駐波比)	0 ~ 4 GHz	1.65 Max.	
Dielectric Withstanding Voltage(絕緣耐電壓)	DC, time: 60sec	1500 Vrms Min.	
Contact Resistance (導體阻抗)	Center Contact (中心導體)	DC 0.2V, 1A	3 mΩ Max.
	Outer Contact(外導體)	DC 0.2V, 1A	2 mΩ Max.
Insulation Resistance(絕緣阻抗)	DC 500V, time: 60sec	5000 MΩ Min.	

**MECHANICAL(機械特性)**

項目	測試條件	測試規格
Force To Engage/Disengage(接合力/脫離力):	N/A	2.5 in-lbs max. / 3 lbs max.
Contact Retention(中心導體承受力):	60mm/min	6 lbs min.

REMARKS(備註)

1. Between CUBE BODY (NO.1) And BODY (NO.4) Must Withstand A 40 lbs. Min. Pull Force And A 15 in-lbs. Min. Torque Force.  
(拉力和扭力測試)。



A	N/A	<i>Dark</i>	<i>Dark</i>	Anel
Issue 版本	Revision 修改記錄	Approved 核准	Checked 審核	Drawn 製定