

**BO-JIANG**

帛江科技股份有限公司

BO-JIANG TECHNOLOGY CO., LTD.

PRODUCT SPECIFICATION (產品規格書)

PART NO.(圖號)	7465NR502BF002B	DATE (日期)	2009 / 10 / 29
TITLE(產品名稱)	TNC R/A PCB MOUNT JACK		

MATERIAL AND FINISH(材質及表面處理)

DESCRIPTION(名稱)	MATERIAL(材質)	FINISH(表面處理)
Center Contact(中心導體)	PHOSPHOR BRONZE	3 μ " GOLD
Insulator(絕緣體)	TEFLON	WHITE
Outer Contact(外導體)	BRASS	70 μ " NICKEL
Others(其它)		

ELECTRICAL(電氣特性)


項目	測試條件	測試規格
Impedance(阻抗)	0 ~ 4 GHz	50 Ω
Voltage Standing Wave Ratio(VSWR)(駐波比)	0 ~ 4 GHz	1.2 Max.
Dielectric Withstanding Voltage(絕緣耐電壓)	DC, time: 60sec	1500 Vrms Min.
Contact Resistance (導體阻抗)	Center Contact (中心導體)	DC 0.2V, 1A
	Outer Contact(外導體)	DC 0.2V, 1A
Insulation Resistance(絕緣阻抗)	DC 500V, time: 60sec	5000 M Ω Min.

MECHANICAL(機械特性)

項目	測試條件	測試規格
Force To Engage/Disengage(接合力/脫離力):	N/A	2 in-lbs. max.

REMARKS(備註)

- Between CUBE BODY (NO.1) And BODY (NO.4) Must Withstand A 40 lbs. Min. Axial Force And A 15 in-lbs. Min. Torque Force.
(軸向力和扭力測試)。
- Between CUBE BODY (NO.1) And INSULATOR (NO.3) Must Withstand A 6 lbs. Min. Axial Force.
(軸向力測試)。
- Between BODY (NO.4) And LOCK RING (NO.6) Must Withstand A 6 lbs. Min. Axial Force.
(軸向力測試)。



A	N/A			
Issue 版本	Revision 修改記錄	Approved 核准	Checked 審核	Drawn 製定